LIVELLO COLLECTION

ACOUSTICAL WALL & CEILING PANELS



L250

NOISE BARRIER WALL PANELS

L250 Noise Barrier Wall Panels are manufactured specifically as double duty acoustical panels that offer both superior sound absorption and noise blocking performance. L250 wall panels are the perfect solution for privacy problems, ensuring that confidential conversations will not be overheard.

L250 panels provide excellent acoustical performance with NRC ratings as high as 1.00 and STC rating as high as 30. Panels are constructed using 1lb. per square foot non-reinforced mass loaded vinyl barrier sandwiched between two layers of a 6-7# PCF rigid fiberglass core and are available in a variety of sizes, thicknesses and edge styles.

Due to panel weight (2.5 lb per square foot), panels must be installed from floor to ceiling. Floor molding can be re-installed after installation.

Conference Rooms

Doctor's Offices

Corporate Offices

Anywhere speech privacy is desired





LIVELLO COLLECTION

ACOUSTICAL WALL & CEILING PANELS



FEATURES

- High NRC and STC Ratings
- Excellent Acoustical Performance
- Class A Fire Rated
- Standard or COM Fabrics
- Various Installation Options
- Custom Sizes and Shapes

TEXTILES

- Guilford of Maine: FR701 & Anchorage
- Micro-perforated Vinyl
- COM (must meet manufacturing requirements)

ACOUSTICS

Thickness	1⅓8"	2 1/8"
NRC Rating	.80 — .90	.90 - 1.00
STC Rating	29	30

DIMENSIONS

Sizes: up to 4' x 10' Thickness: $1 \frac{1}{8}$ or $2 \frac{1}{8}$

SUBSTRATE

1 lb. per sq.ft. non-reinforced mass loaded vinyl barrier sandwiched between two layers of a 6-7# PCF rigid fiberglass core

FIRE RATING

All components have a Class A fire rating per ASTM E-84

INSTALLATION OPTIONS

Panels must be installed from floor to ceiling due to their weight of 2.5 lbs. per square feet.



Rotofast Anchors




Impaling Clips




Adhesive

EDGE STYLES









AKOUO-ACOUSTICS.COM a division of Sedia Systems

AKOUO

acoustics