

Recycled Content  
Bleach Cleanable

Panel | Acoustic

# FR701® 2100

Panel | Acoustic

White 224	Eggshell 144	Bone 748	Wheat 130	Quartz 380	Pearl 481
Yellow 744	Lime 721	Fir 743	Verte Papier 561	Opal 394	Desert Sand 758
Sunshine 797	Sky 740	Teal 742	Coin 794	Silver Papier 538	Cement Mix 750
Orange 746	Sapphire 745	Ultramarine 470	Blue Papier 539	Grey Mix 238	Silver Neutral 406
Cardinal 738	Cobalt 420	Wedgewood 150	Crystal Blue 175	Flannel 795	Moleskin 796
Red 799	Iris 798	Baltic 153	Steel Grey 471	Medium Grey 298	Black 408



# FR701® 2100

## Specifications

<b>Content</b>	100% post-consumer recycled polyester
<b>Weight</b>	16.0 ± 0.5 oz./lin. yd
<b>Width</b>	66" min. useable
<b>Repeat</b>	none

## Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

**Bleach Cleanable** - May be cleaned with a 10% bleach-to-water solution. Rinse well after cleaning. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

## Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- This is a non-directional fabric.

**Proudly woven in North America supporting our local communities.**

## Sustainability

100% recycled and recyclable



Renowned for its exceptional performance and style, Guilford of Maine has set industry standards in acoustics and panel fabrics for many decades. We present the Guilford of Maine Collection - a selection of timeless fabrics.



USA & INTERNATIONAL | T 800-544-0200  
CANADA | T 418 227-9897  
For samples, visit [duvaltalex.com](http://duvaltalex.com)

## Performance

- Colorfastness to light (AATCC 16.3 Option 3)**  
Grade 4 min. at 40 hours
- Colorfastness to crocking (AATCC 8)**  
Grade 4 min. dry & Grade 3 min. wet
- Breaking Strength (ASTM D5034)**  
150 lbf min. warp and fill
- Flammability**  
ASTM E84 Class I or A

## Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

**Acoustic Transparency:** 95%

For more detailed results, please consult our website.

This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

Certification Marks owned by the Association for Contract Textiles, Inc.

Recycled Content

Seating | Panel | Acoustic

## Anchorage 2335 | Open House 2334

White\*  
2664

Shadow†  
6694

Birch  
2129

Vanilla  
2130

Angora  
2035

Asteroid  
2053

Goose  
2049

Fossil  
2093

Graphite  
2079

Coffee Bean  
2083

Slate  
2017

Wolf  
2027

Quarry Blue  
2026

Lapis  
2094

Deep Water  
2051

Waterfall  
2691

Pool  
2842

Thistle  
2085

Cobalt  
2045

Midnight  
2025

Cumin  
2050

Eucalyptus  
2047

Willow  
2028

Green Apple  
2087

Fern  
2840

Turquoise  
2841

Pine Needle  
2022

Onyx  
2016

Aubergine  
2036

Straw  
2034

Lemon  
2839

Sunshine  
2082

Goldenrod  
2090

Pumpkin  
2021

Geranium  
2084

Red Delicious  
2014

Poppy  
2091

Orchid  
2843

Mulberry  
2044

\*Not recommended for use as Upholstery.

# Anchorage 2335 Open House 2334

Seating | Panel | Acoustic

## Specifications

<b>Content</b>	65% pre-consumer recycled polyester 35% post-consumer recycled polyester
<b>Weight</b>	2334 - 13.1 ± 1.0 oz./lin. yd 2335 - 15.0 ± 1.0 oz./lin. yd
<b>Width</b>	2334 - 54" min. useable 2335 - 66" min. useable
<b>Repeat</b>	none

## Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

## Miscellaneous

- Application testing of this product is recommended.
- Colors may vary between dye lots.
- Please specify when ordering whether 54" or 66" width is needed. Dye lots may vary. Differences may also occur between corresponding colors of Anchorage 2335 and Open House 2334.

**Proudly woven in North America supporting our local communities.**




## Sustainability

100% recycled and recyclable



Renowned for its exceptional performance and style, Guilford of Maine has set industry standards in acoustics and panel fabrics for many decades. We present the Guilford of Maine Collection - a selection of timeless fabrics.

## Performance


	<b>Colorfastness to light (AATCC 16.3 Option 3)</b> Grade 4 min. at 40 hours
	<b>Colorfastness to crocking (AATCC 8)</b> Grade 4 min. dry & Grade 3 min. wet
	<b>Breaking Strength (ASTM D5034)</b> 275 lbf min. warp and fill
	<b>Seam Slippage (ASTM D4034)</b> 50 lbf min. warp and fill
	<b>Pilling Resistance (ASTM D3511)</b> Class 4 min.
	<b>Flammability</b> CA Technical Bulletin 117-2013 Section 1 ASTM E84 Class I or A
	<b>Abrasion (ASTM D4157)</b> 250,000 double rubs min. cotton duck

## Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

**Acoustic Transparency:** 85%

For more detailed results, please consult our website.

 This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized fabric is not required on approved panels from participating manufacturers.

\*Multiple factors affect fabric durability and appearance retention, including end-user application and proper maintenance. Wyzenbeek results above 100,000 double rubs have not been shown to be an indicator of increased lifespan.

Certification Marks owned by the Association for Contract Textiles, Inc.

†Available in 66" only.

duvaltex

USA & INTERNATIONAL | T 800-544-0200  
CANADA | T 418 227-9897  
For samples, visit [duvaltex.com](https://www.duvaltex.com)